

M.G. Concrete Pump MXRZ49–5.16

Description:

M.G. Concrete pump type MXRZ49–5.16, Part No. 9495001
Without a truck / Mounted on a XXX truck model XXXX

Technical Details:

- Max. Concrete capacity: 158 m³/hr
- Max. Concrete pressure: 72 (115) bar
- Hydraulic cylinder diameter: 130/80 mm
- Concrete pumping cylinders: 2100/230 mm
- Main Hydraulic pump manufactured by REXROTH HYDROMATIC A11VLO: 260 liter
- Open Hydraulic System
- Transfer gear box: 1:1.19 low ratio
- Oil tank: 550 liters
- Boom control valve proportional manufactured by HAWE
- Monoblocks manufactured by HAWE
- Water tank: 600 liters
- Hopper capacity: 600 liters
- Water pump manufactured by GRUNDFUS: 120liter/min – 20 bar
- Wire remote control: 40 meter
- Oil Cooler manufactured by EMMEGI
- Proportional radio remote control manufactured by Hetronic
- Central lubrication strip hopper
- Concrete line DN 125 5.5
- Connection for filling water tank
- Chassis horn via remote control & hopper
- Engine speed adjustment from remote control
- Hand held spotlight
- Hinged cast elbow with connection for cleaning
- Operating manuals and spare parts book
- Painting pump: Yellow
- Painting boom: Red
- Aluminum hopper cover
- Rubber collar on hopper
- Set of tools
- Spray hose with bracket
- 4 support plates in magazine
- Tool box
- Towing eye
- Water spray jet with 10 meter hose

Boom specification:

5 arms – “RZ” type

Vertical reach	48.3 meter
Horizontal reach	44.7 meter
Slewing range (Rotation)	370 °
Reach depth	35.7 meters
Unfolding height	9.5 meters
Front support legs width	9.2 meters
Rear support legs width	11.04 meters
Length of end hose	4 meter
X type Outrigger	

Country of origin: South Korea